DM[™]604 S2 Floor-standing loudspeaker system

Product Summary

- The DM604 S2 is an excellent choice for high performance hi-fi systems or as a front channel speaker in a sophisticated Home Cinema system.
- The DM604 S2 has a aluminium dome tweeter, one woven Kevlar[®] cone mid-range driver and two paper/Kevlar[®] cone bass drivers. The second cone is specifically tailored to extend low frequency response and increase power handling.
- The two bass drivers incorporate our mushroom dustcap construction, where the whole diaphragm structure is stiffened in girder fashion by using a larger diameter dustcap.

Technical highlights



Nautilus[™] Tweeter: B&W's Nautilus Tweeter technology ensures that the sound remains focused and time-sensitive and that the stereo-image is presented with unparalleled three dimensional accuracy.



Kevlar®: B&W developed and patented the method of using Kevlar® for loudspeaker cones to reduce unwanted standing waves. DuPont originally created Kevlar® for use in bulletproof vests.



| Description | 3-way vented-box system | Nominal impedance | 8 (min 3) |
|--------------------|------------------------------------|-------------------|-------------------------------------|
| Drive units | 1 x 25mm metal dome high-frequency | Power handling | 25W - 200W into 8 ohm on unclipped |
| | 1 x 180mm woven Kevlar® cone | | programme |
| | bass/midrange | Dimensions | Height: 996mm Width: 236mm |
| | 2 x 180mm paper/Kevlar® cone bass | | Depth: 411mm |
| Frequency response | 44Hz – 20kHz ± 3dB on reference | Finishes | Cabinet: Cherry or Black Ash Vinyl, |
| | axis | | Grilles: Black cloth |
| Sensitivity | 90dB spl (2.83V, 1m) | | |
| | | | |

